

# EventDeck

## PRODUCT SPECIFICATIONS

- Module Size:**                      **Width:** 4" / 10.16 cm / 101.6 mm  
**Length:** 12" / 30.48 cm / 304.80 mm  
3 connected modules = 12" x 12" / 304.8 mm x 304.8 mm  
**Thickness:** ¾" Tall / 1.91 cm / 19.05 mm
- Module Weight:** 0.27 lbs. / 4.3 oz. / 0.12 kg. / 122 grams  
**Per Square Foot:** 0.81 lbs. / 12.96 oz. / 0.37 kg. / 367.41 grams  
**Per Square Meter:** 8.72 lbs. / 3.95 kg.
- Material:** High-impact polypropylene co-polymer. UV Inhibitors added.
- Fire Rating:** UL 94HB (Underwriters Laboratory Yellow Card Number)  
This test signifies that this product does not flare up when exposed to an open flame and has a slow burn rate of 2" per minute for a 2" wide, 0.5 millimeter thickness test sample. EventDeck meets applicable standards for temporary floor covers.  
ASTM 2859 (Flammability of Finished Texture Floor Covering Materials)  
– passed test  
\* Testing reports available for fire ratings
- Hot Wire Ignition Rating:** 3
- Melting Point:** 324 Fahrenheit / 162 Celsius  
**Operating Range:** -10° F → 150°F / -23.33° C → 65.56° C
- Support Structure:** Flooring module incorporates multi-directional structural support ribbing, allowing for distribution of weight and loads. There are no open spans (without ribs) greater than 2.125".
- Weight Loading:** 8,000 lbs sq/ft static load, solid sub-surface. Varies depending on sub-surface.
- Ground Surfaces:** EventDeck is designed to be used with little ground preparation el, sand, soil, concrete, asphalt, ice, snow, mud, synthetic turf, rubberized tracks, and other standard surfaces.
- Shipping:** 40" x 48" Pallet: up to 1,000 sq/ft  
463L Pallet: 7,776 sq/ft  
20' Ocean Container: 12,340 sq/ft  
40' Ocean Container: 27,380 sq/ft  
Note: High cube container loads can be loaded with additional product.



**Signature Systems Group, LLC**  
50 East 42<sup>nd</sup> Street • 14th Floor  
New York, NY 10017

Toll Free: 800-569-2751 • 212-953-1116 • Fax: 212-953-1117  
Flooring: [www.eventdeck.com](http://www.eventdeck.com) • Fencing: [www.signaturefencing.com](http://www.signaturefencing.com)

**Functional Features:**

- a) Sections are designed to roll up for easy installation, removal, storage and transport.
- b) Individual modules interconnect to form larger flooring sections.
- c) Connection system allows for installation and disassembly *without* the need for connection or separation tools.
- d) Modules feature integrated, multi-directional cable channels on the underside of each tread, for running power and communication wiring or rope lighting.
- e) Modules are designed to allow 90-degree rotation and still connect. Module can be connected in both directions and at any module connection point, allowing greater flexibility in floor design.
- f) Modules do not have any submerged channels into which debris or dirt can enter from the top surface, and are easy to clean and maintain.

**Grass Protection**

**Features (ED1):**

- a) Modules feature an integrated moisture canopy which allows for moisture retention.
- b) EventDeck features direct-from-the-top drainage holes that provide drainage, ventilation, air, and small amounts of light to grass below.
- c) Underside is specially designed to protect grass and other sensitive surfaces by distributing weight across multiple support ribs. No sharp, unsupported edges exist to damage grass or synthetic turf.

**Warranty:**

3-year warranty against manufacturer's defects.

**National Stock #:**

8340-01-525-4069

**EVENTDECK ACCESSORIES SPECIFICATIONS**

**Edging**

**Specifications:**

Edging size is 3" x 12" x 3/4" (tapered). Edging is designed to attach to flooring modules both lengthwise and widthwise, providing a gradual tapered edge. Edging extends flat 1" from end of flooring module and then slopes down to ground over a 2" span.



**Signature Systems Group, LLC**  
50 East 42<sup>nd</sup> Street • 14th Floor  
New York, NY 10017

**Toll Free: 800-569-2751 • 212-953-1116 • Fax: 212-953-1117**

**Flooring: [www.eventdeck.com](http://www.eventdeck.com) • Fencing: [www.signaturefencing.com](http://www.signaturefencing.com)**